



PANEL CUTOUT  
 $\varnothing 12.5$

NOTE : SECOND ADJUST SWITCH  
 SHOULD BE MADE IN THE PROPER POSITION  
 ON THE PANEL

SH.T. NO.

TERMINAL BLOCK



AC  
 E.L. ] AC POWER SOURCE FOR E.L.

WIRING DIAGRAM

This drawing is the property of CMR KOREA Co.,Ltd. and must not be wholly or partly copied, reproduced, utilized or published without written consent.  
 This is a CADAM drawing and should not be corrected by hand.

GENERAL TOLERANCE FOR BOX OUTLINE

GENERAL TOLERANCE FOR SENSOR & FITTING HOLE

NOMINAL MEASURE	TOLERANCES	NOMINAL MEASURE	TOLERANCES
OVER 1	$\pm 1.0$	1	$\pm 0.3$
100	$\pm 2.0$	4	$\pm 0.5$
200	$\pm 3.0$	16	$\pm 1.0$
500	$\pm 5.0$	63	$\pm 2.0$
1000	$\pm 7.0$	250	$\pm 2.5$

REV.	LOC.	DATE	TITLE
△			30 SEC SLAVE CLOCK WITH SECOND HAND (SSC-103)
△			

NOTE

APPD	20001004	P. H. LEE	REV.	0
CHKD			UNIT	mm
DWG.	20001004	S. J. LEE	SCALE	N / S

SIZE	A4	DRAWING NO.	ETCSC-01001
		<b>CMR KOREA CO., LTD.</b>	